



DTT-L Series Digital Torque Testers

New Standard DTT-L (Lite) Torque Testers



- $\pm 0.5\%$ of full scale accuracy
- Dimensions*: 7.1in x 4.3in x 2.1in (181mm x 111mm x 54mm)
- Weight*: 4.8 lb (2.2 kg)
- 6-7 torque units selectable depending on model
- 3 modes of Operation: Track, Peak, and First Peak
- 200 readings stored in memory
- 3/8" female square drive
- Reads clockwise or counterclockwise
- Calibration certificate traceable to N.I.S.T.
- **Multiple Functions:** Auto Reset, Auto Memory, Auto Zero, Real Time Clock, Pass/Fail Statistics, Torque Bar, Battery Indicator, Charging Status Indicator, and Transducer State
- Not for use with impact or pulse tools
- 9 VDC, 500 mA, 90-264 VAC US Power Adapter (ASG #66603) supplied – International charger (ASG #66619) supplied with -INTL models
- Complete selection of rundown adapters available

Model Number	ASG Number	Torque Range	
		lbf.in	N.m
DTT-L 5	66650	0.5 - 5.0	0.06 - 0.56
DTT-L 10	66651	1.0 - 10.0	0.11 - 1.13
DTT-L 30	66652	3.0 - 30.0	0.33 - 3.4
DTT-L 50	66653	5.0 - 50.0	0.56 - 5.6
DTT-L 100	66654	10.0 - 100.0	1.13 - 11.3
DTT-L 200	66655	20.0 - 200.0	2.3 - 22.6
DTT-L 500	66657	50.0 - 500.0	5.6 - 56.5

* Dimensions of DTT-L 200 and DTT-L 500 with mounting plate: 8.6in x 4.3in x 2.1in (219mm x 111mm x 54mm); Weight: 6.6lb (3 kg)

⚠ WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov

Quality Certified ISO 9001:2008
ASG, Division of Jergens, Inc.
Jergens Way, 15700 S. Waterloo Road
Cleveland, OH 44110-3898
Toll Free: (888) 486-6163 | Fax: (216) 481-4519
Email: asginfo@asg-jergens.com | www.asg-jergens.com

